



OZINGA®

OzingaShield

REDUCE WATER PENETRATION AND INCREASE LONG-TERM DURABILITY

OzingaShield is an integral concrete sealer that drastically reduces water penetration, increases long-term durability, improves color vibrancy in integrally colored concrete, and starts protecting from day one. Rather than sealing weeks after installation, OzingaShield protects like a topically sealed pavement from the day it is poured.

OZINGASHIELD IS PERFECT FOR:

- Driveways
- Patios
- Front walks
- Stoops
- Sidewalks
- Stairs

BENEFITS OF OZINGASHIELD:

- Provides protection through full depth of concrete
- No applying or additional work for contractors
- Sealer prevents water ingress in slab
- Can be added to any concrete

INTERESTED IN OZINGASHIELD? CHECK OUT OUR SPECIALIZED FLATWORK MIX SERIES - OZFLAT!:

OZFLAT LITE

4000 PSI (5-8% AIR)
0.45 WATER TO CEMENT RATIO
STANDARD WATER REDUCER
CRUSHED LIMESTONE AGGREGATE
OZINGASHIELD

Mix Number: **OZFLATLITE**

OZFLAT

BEST VALUE

4500 PSI PER ACI RECOMMENDATIONS FOR EXTERIOR FLATWORK (5-8% AIR)
0.42 WATER TO CEMENT RATIO
MID RANGE WATER REDUCER FOR ENHANCED FINISHABILITY
CRUSHED LIMESTONE AGGREGATE
MICRO FIBERS FOR REDUCTION IN SHRINKAGE CRACKING
SLUMP RETENTION ADMIXTURE
OZINGASHIELD

Mix Number: **OZFLAT**

OZFLAT PREMIUM

5000 PSI (5-8% AIR)
0.40 WATER TO CEMENT RATIO
MID RANGE WATER REDUCER FOR ENHANCED FINISHABILITY
CRUSHED LIMESTONE AGGREGATE
MICRO FIBERS FOR REDUCTION IN SHRINKAGE CRACKING
SLUMP RETENTION ADMIXTURE
SHRINKAGE REDUCING ADMIXTURE FOR ADDITIONAL CRACK REDUCTION
OZINGASHIELD

Mix Number: **OZFLATPRE**

Place your order today. Contact your Ozinga sales representative or visit ozinga.com.

All ACI and standard concrete placement and jointing practices should be followed in the use of any of the above branded mix designs for optimal performance.