



# LIQUID RELEASE

**Product Description:** Ozinga liquid release is a bubble gum scented colorless liquid release agent specially formulated as a bond breaker between freshly poured concrete and decorative tools such as stamp mats, texture skins, stencils, Etc. It creates a lubricating barrier that extends the life of the texturing tools by decreasing the friction between the concrete and the tools. Ozinga Liquid Release evaporates leaving no residue behind, meaning less clean-up and labor cost. This characteristic makes it perfect for both exterior and interior applications.

**Features & Benefits:**

- Great for use with Stamps
- Pleasant bubblegum scent
- Low viscosity, sprayable formula

**Composition:** Clear

**Mixing:** Stir well before using. Material may separate during long term storage.

**Physical Properties at 70° F (21°C):**

Weight per gallon:

pH:

Color:

**Approximate Values:**

8.34 lbs (+/- 0.25 lbs) /gal

8.00 (+/- 0.50)

Clear solution

**Directions for Use:** Apply Ozinga Liquid Release to the surface or stamping mats at a rate of 750 square feet per 5 gallon pail, or 150 square feet per gallon to allow easy removal of stamping mats, stencils, and patterns. Also retards the surface for longer workability and can be used with color hardeners for a great antique finish.

**Cautions:** Ozinga Liquid Release is a flammable liquid. Before using, the applicator should read all label, technical data and safety information completely. Recommended for exterior use only. For professional use only. Keep away from children.

**Warnings:** Flammable liquid. Toxic to aquatic life with long lasting effects. Causes serious eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness. May be harmful if swallowed. May be harmful if swallowed and enters airways. Causes skin irritation. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat / sparks / open flames / hot surfaces. No smoking. Keep container tightly closed. Ground / bond container and receiving equipment. Use explosion-proof electrical / ventilating / lighting / equipment. Use only non-sparking tools. Take action to prevent static discharges. Avoid breathing dust / fume / gas / mist vapors / spray. Wash face, hands and any exposed skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves / protective clothing / eye protection / face protection. IF exposed or concerned: Get medical advice / attention. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water / shower. If skin irritation occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contacts, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice / attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. IF SWALLOWED: Immediately call a POISON CONTROL CENTER / Doctor. Do NOT induce vomiting. Take off contaminated clothing and wash before reuse. In case of fire use, "alcohol resistant" foam, dry chemical, halon or carbon dioxide to extinguish. Collect spillage.

**HMIS Codes:** HEALTH = 1, FLAMMABILITY = 2, REACTIVITY = 0, P. PROTECTION = C

**Shelf Life:** 1 year properly stored at 40° to 80° F

**Limited Warranty:** This product is warranted to be of merchantable quality when used according to the instruction herein. It is not warranted to be suitable for any purpose or use other than the general purpose for which it is intended. Liability under this warranty is limited to the replacement of the product as purchased, if found to be defective upon inspection by the manufacturer. This limited warranty is issued and accepted in lieu of all other expressed warranties and explicitly excludes liability for consequential damages. Buyer assumes all risk and liability resulting from the use of this product.